



New 26 & 26A Series Steel Monotube Shocks



For Circle Track Racing

- **Linear, Digressive and Low Speed Super Digressive Valving Available**
- **Racer Revalveable & Rebuildable**
Designed for unparalleled repeatability.
- **Available Sealed**
Available sealed to meet the requirements of certain series such as IMCA. Add "A" to part number (e.g. 26A75).
- **Tuneable Gas Pressure**
External gas charging port allows quick adjustments to gas pressure for varying track conditions.
- **Non-Fading**
Very consistent gas pressures, even on rough tracks and during long races.
- **One-Piece Body Design**
- **46mm Piston**
Large piston creates unmatched valving consistency for all shaft velocities.
- **15mm Centerless Ground, Hard Chrome Plated, Gun-Drilled Piston Rod**
Precision surface eliminates piston rod flex, increasing valving consistency.
- **Deflective Disc Valving**
Provides consistency in production and performance throughout entire velocity range.
- **Can Be Run Upside Down**
Can be mounted upside down with no change in rate to reduce unsprung weight.
- **Replaceable 1/2" I.D. Bearings**

With the Tuning Kit (part #TK08) you can

Coil-Over Sleeve Kits sold separately:

Part #CK2605 7" Stroke

Part #CK2607 9" Stroke

Part #CK2609 Premium Kit with Spring Glider for 5" O.D. Springs - 7" & 9"

Order a Spanner Wrench (part #T114W) for easy ride height adjustments

Don't forget a Rebuild Kit (part #RK11)

Other accessories include:

Fill Tool (part #7791-140)

Body Clamp (part #7791-143)

7" STROKE - DIGRESSIVE VALVING

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 2673 | 3 | 13.00 | 20.00 |
| 2673-5 | 3-5 | 13.00 | 20.00 |
| 2673-7 | 3-7 | 13.00 | 20.00 |
| 2674 | 4 | 13.00 | 20.00 |
| 2675 | 5 | 13.00 | 20.00 |
| 2675-3 | 5-3 | 13.00 | 20.00 |
| 2676 | 6 | 13.00 | 20.00 |
| 2676-4 | 6-4 | 13.00 | 20.00 |
| 2677 | 7 | 13.00 | 20.00 |
| 2677-3 | 7-3 | 13.00 | 20.00 |
| 267X** | Specify | 13.00 | 20.00 |

7" STROKE - LOW SPEED SUPER DIGRESSIVE VALVING

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 2675-7H | 5-7 | 13.00 | 20.00 |
| 2675-8H | 5-8 | 13.00 | 20.00 |
| 2675-10H | 5-10 | 13.00 | 20.00 |
| 2675-12H | 5-12 | 13.00 | 20.00 |
| 2675-13H | 5-13 | 13.00 | 20.00 |

9" STROKE - DIGRESSIVE VALVING

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 2693 | 3 | 15.00 | 24.00 |
| 2693-5 | 3-5 | 15.00 | 24.00 |
| 2694 | 4 | 15.00 | 24.00 |
| 2695 | 5 | 15.00 | 24.00 |
| 2696-2 | 6-2 | 15.00 | 24.00 |
| 2697-2 | 7-2 | 15.00 | 24.00 |
| 2698-2 | 8-2 | 15.00 | 24.00 |
| 2699-1B* | 9-1 | 15.00 | 24.00 |
| 2699-3 | 9-3 | 15.00 | 24.00 |
| 269X** | Specify | 15.00 | 24.00 |

9" STROKE - SEALED PER CERTAIN SANCTIONING BODIES (E.G. IMCA)

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 26A93 | 3 | 15.00 | 24.00 |
| 26A93-5 | 3-5 | 15.00 | 24.00 |
| 26A93M | Linear | 15.00 | 24.00 |
| 26A94 | 4 | 15.00 | 24.00 |
| 26A95 | 5 | 15.00 | 24.00 |
| 26A96-2 | 6-2 | 15.00 | 24.00 |
| 26A96-2M | 6-2 Linear | 15.00 | 24.00 |
| 26A97-2 | 7-2 | 15.00 | 24.00 |
| 26A99-3 | 9-3 | 15.00 | 24.00 |

*Axle Damper

7" STROKE - LINEAR VALVING

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 2673-5M | 3-5 | 13.00 | 20.00 |
| 2673M | 3 | 13.00 | 20.00 |
| 2673-7M | 3-7 | 13.00 | 20.00 |
| 2674M | 4 | 13.00 | 20.00 |
| 2675M | 5 | 13.00 | 20.00 |
| 2675-3M | 5-3 | 13.00 | 20.00 |
| 2676M | 6 | 13.00 | 20.00 |
| 2677M | 7 | 13.00 | 20.00 |
| 2677-3M | 7-3 | 13.00 | 20.00 |
| 267xM** | Specify | 13.00 | 20.00 |

7" STROKE - SEALED PER CERTAIN SANCTIONING BODIES (E.G. IMCA)

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 26A73-5 | 3-5 | 13.00 | 20.00 |
| 26A73-5M | 3-5 Linear | 13.00 | 20.00 |
| 26A73-7 | 3-7 | 13.00 | 20.00 |
| 26A75 | 5 | 13.00 | 20.00 |
| 26A75-3 | 5-3 | 13.00 | 20.00 |
| 26A75-3M | 5-3 Linear | 13.00 | 20.00 |
| 26A75M | 5 Linear | 13.00 | 20.00 |
| 26A76 | 6 | 13.00 | 20.00 |
| 26A76-4 | 6-4 | 13.00 | 20.00 |

9" STROKE - LINEAR VALVING

| Part Number | Valving Comp./ Rebound | Compressed Length | Extended Length |
|-------------|------------------------|-------------------|-----------------|
| 2693M | 3 | 15.00 | 24.00 |
| 2693-5M | 3-5 | 15.00 | 24.00 |
| 2694M | 4 | 15.00 | 24.00 |
| 2695M | 5 | 15.00 | 24.00 |
| 2696-2M | 6-2 | 15.00 | 24.00 |
| 2697-2M | 7-2 | 15.00 | 24.00 |
| 2698-2M | 8-2 | 15.00 | 24.00 |
| 269xM** | Specify | 15.00 | 24.00 |

CAUTION!
Shock under pressure.
Release pressure *before*
removing closure nut.

**Custom valving available at an additional charge